

POWER MULTIROW SINGLE CENTRAL DROP LINE LT 1000 - LT 1500 - LT 2000

ARTICULATED LOW VOLUME ATOMIZER:
For rows from 2.00 metres to 2.50 metres
composed of 3 drop lines with 18 outlets with
54 outputs equipped with manual control for
independent closure of the treatment liquid and
of the air

STAINLESS RANGE
FOR TRACTORS \geq CV 75 - 55 KW



BASIC STANDARD EQUIPMENT WITH:

- Hot galvanised steel frame treated with high-grip base, metallic paint and transparent protection
- Central and side protection, height-adjustable hubs
- High density polyethylene tank complete with product mixer, level indicator, handwashing tank, circuit washing and can washing
- Steering capability 220°
- Fan housing made of hot galvanised sheet steel and painted
- Centrifugal closed blade fan in sheet steel Ø 550 mm, air volume up to 22000 mc/h
- Disengagement and centrifugal clutch on the fan shaft
- Mechanical step-up gear with oil-bath gears and 2 speed gearbox
- Anodised aluminium 3 membrane pump, flow rate 130 lt/min, 20 bar
- 4 solenoid valves with electrical remote control for opening/closing the liquid
- Pressure gauge and electrical pressure regulator

BASIC STANDARD EQUIPMENT

POWER.MULTI.ROW.S.1000	Tank lt. 1000 Rubberising 10.0/80 – 12
POWER.MULTI.ROW.S.1500	Tank lt. 1500 Rubberising 10.0/75 – 15.3
POWER.MULTI.ROW.S.2000	Tank lt. 2000 Rubberising 10.0/75 – 15.3

ACCESSORIES ON REQUEST ORDERED AND INSTALLED AT THE ORIGIN

ACCESS.52	Universal joint cv 60-700 mm
ACCESS.15	Fill tube (filter and bottom valve)
ACCESS.24	Kit version Toscana: steel central and side moulding, adjustable-height hubs, rubberising 10.0/75-15.3
ACCESS.25	Electrical pressure regulator with remote control
ACCESS.26.M	4-way electronic computer for automatic feed control provided with membrane pump
ACCESS.41	Rubberising difference 400/60 - 15.5 to 6 holes
ACCESS.63	Puncture treatment for pair of wheels
ACCESS.69	6-fan columns with independent closing the air and the liquid
ACCESS.EL	Electrostatic system for the positive charge of the treatment flow

MODEL	Minimum height	Standard height	Variable height	Width	Length	Weight
Power Multirow	220 cm	220 cm	-	205 cm	165 cm	540 kg