

VS 50

LT 600 - LT 1000

LOW VOLUME ARTICULATED ATOMIZER
POLYETHYLENE RANGE
FOR TRACTORS \geq CV 50 - 37 KW



Basic standard equipment with:

- Frame in treated tubular steel treated with high-grip base, metallic paint and transparent protection
- Steering capability 220°
- High density polyethylene tank lt. 600 or lt. 1000 complete with product mixer, level indicator, handwashing tank, circuit washing and can washing
- Distribution devices in high density polyethylene with vertical movement of 70°
- Fan housing in high density polyethylene with two independent outputs
- Centrifugal closed blade fan in sheet steel Ø 500 mm, air volume up to 13200 mc/h
- Mechanical step-up gear with oil-bath gears and 2 speed gearbox
- Disengagement and centrifugal clutch on the fan shaft
- Self-priming stainless pump with automatic belt tensioner, flow rate 200 lt/min.
- 2 Solenoid valves with remote electrical control, pressure gauge and manual pressure regulator
- Litre-counter dispensers with graduated scale in stainless steel for each sector





BASIC STANDARD EQUIPMENT

VS.50.600	Tank lt. 600 Rubberising 185/65 – 14
VS.50.1000	Tank lt. 1000 Rubberising 10.0/80 – 12

ACCESSORIES ON REQUEST ORDERED AND INSTALLED AT THE ORIGIN

ACCESS.52	Universal joint cv 60-700 mm
ACCESS.15	Fill tube (filter and bottom valve)
ACCESS.57	Central and side protection, adjustable hubs
ACCESS.25	Electrical pressure regulator with remote control
ACCESS.26.C	Electronic computer for automatic feed control provided with stainless steel centrifugal pump
ACCESS.70.V	4 V.M.A. solenoid valves to control liquid opening-closing
ACCESS.70.A	4 solenoid valves ARAG to control liquid opening-closing
ACCESS.56	Hydraulic movement of the upper distribution devices equipped with hydraulic lines with quick coupling
OMOLOGAZIONE VS	Classification for road circulation tank lt 1000 at full load with direct hooking to the tractor (special drawbar, lights, foot rest, license plate holder)
ACCESS.EL	Electrostatic system for the positive charge of the treatment flow

DISTRIBUTION DEVICES IN HIGH DENSITY POLYETHYLENE PROVIDED WITH LITRE-COUNTER DISPENSERS WITH GRADUATED SCALE IN STAINLESS STEEL WITH ANTIDRIP DEVICE

	2V.ST	2 lower fans (8 sectors in stainless steel)
	2C2V.ST	2 upper guns 2 lower fans (8 sectors in stainless steel)
	4V.ST	2 upper fans (8 sectors in stainless steel) 2 lower fans (8 sectors in stainless steel)
	3T.ST 3TG.ST	Vertical movement hydraulic gun with 3 dispensers and hydraulic lines Vertical and swivel movement hydraulic gun with 3 dispensers and hydraulic lines

NEW LITRE-COUNTER DISPENSERS IN STAINLESS STEEL WITH GRADUATED SCALE FOR EACH SECTOR PROVIDED WITH THE EQUIPMENT



MODEL	PLLPXPKHLKW	VWDGDUGKHLKW	DULDEOHKHLKW	ZLGWK	OHWK	ZHLKW
VS 50	140 cm	240 cm	-	110 cm	130 cm	265 kg