

Fast 50

LT 300-LT 400-LT 600

MOUNTED LOW VOLUME ATOMIZER
STAINLESS RANGE
FOR TRACTORS \geq CV 50-37 KW



Basic standard equipment with:


- Frame in treated tubular steel treated with high-grip base, metallic paint and transparent protection, predisposed for a pair of wheels
- Tank in high density polyethylene lt. 300 or lt. 400 complete with product mixer, level indicator, plant washing and handwashing tank
- Fan housing made of hot galvanised sheet steel and painted
- Stainless steel distribution devices with vertical movement of 70°
- Centrifugal closed blade fan in sheet steel Ø 500 mm, air volume up to 13200 mc/h, speed up to 80 m/sec
- Mechanical step-up gear with oil-bath gears and 2 speed gearbox
- Self-priming stainless pump with automatic belt tensioner, flow rate 200 lt/min.
- 2 Solenoid valves with remote electrical control, pressure gauge and manual pressure regulator
- Litre-counter dispensers with graduated scale in stainless steel for each sector

BASIC STANDARD EQUIPMENT

FAST.50.300	Tank lt. 300 in high density polyethylene
FAST.50.400	Tank lt. 400 in high density polyethylene
FAST.50.600	Tank lt. 600 in high density polyethylene

ACCESSORI A RICHIESTA ORDINATI E MONTATI ALL'ORIGINE

ACCESS.08	Universal joint cv 60-800 mm
ACCESS.15	Fill tube (filter and bottom valve)
ACCESS.02	Pair of wheels with hubs
ACCESS.70.V	4 V.M.A. solenoid valves to control liquid opening-closing
ACCESS.70.A	4 solenoid valves ARAG to control liquid opening-closing
ACCESS.56	Hydraulic movement of the upper distribution devices equipped with hydraulic lines with quick coupling
ACCESS.EL	Electrostatic system for the positive charge of the treatment flow



DISTRIBUTION DEVICES AND LITRE-COUNTER DISPENSERS WITH GRADUATED SCALE STAINLESS STEEL WITH ANTIDRIP DEVICE

	2V.F50	RDVFRVLVDLVV
	2C2V.F50	SSV RDVFRVLVDLVV
	4V.F50	2 upper fans (8 sectors in stainless steel) 2 lower fans (8 sectors in stainless steel)
	2CV.T.F50	2 cannoni laterali e ventaglio centrale, ideale per trattamenti su impianti a tendone
	3T.F50 3TG.F50	Cannone idraulico a movimento verticale, con 3 diffusori e tubazioni idrauliche Cannone idraulico a movimento verticale e girevole 200° con 3 diffusori e tubazioni idrauliche

NEW LITRE-COUNTER DISPENSERS IN STAINLESS STEEL WITH GRADUATED SCALE FOR EACH SECTOR PROVIDED WITH THE EQUIPMENT



MODELLO	altezza minima	altezza standard	altezza variabile	larghezza	lunghezza	Peso
Fast 50	130 cm	230 cm	-	115 cm	150 cm	290 kg