

GRD

600 - 1000

TRAILED WEEDER
RANGE FOR TRACTORS \geq CV 10 - 8 KW



Basic standard equipment with:

- Tubular steel frame
- High density polyethylene tank lt. 600 or lt. 1000 complete with product mixer, level indicator, handwashing tank
- Footrest with handcrank
- Manual control with 2/3 faucets (under-row/total)
- 3-membrane pump
- Manual pressure regulator
- Pressure gauge
- Adjustment of the flow rate by means of nozzles (with replacement of same for flow change)
- Power required for power takeoff CV 5 - 3.5 KW

BASIC STANDARD EQUIPMENT

GR.D.600	Tank lt. 600 Rubberising 185/65 – 14
GR.D.1000	Tank lt. 1000 Rubberising 10.0/80 – 12
OMOLOGAZIONE.POWER	Classification for road circulation truck lt 1000 at full load with direct hooking to the tractor (special steering, lights, foot rest, license plate holder)

ACCESSORIES ON REQUEST ORDERED AND INSTALLED AT THE ORIGIN

ACCESS.04	Universal joint cv 40-1000 mm
------------------	-------------------------------

MODEL	minimum height	standard height	variable height	width	length	weight
GRD.600	148 cm	148 cm	-	110 cm	195 cm	180 kg
GRD.1000	148 cm	148 cm	-	142 cm	195 cm	220 kg