

Optima

LT1500-LT2000

LOW VOLUME TOWED ATOMIZER
STAINLESS RANGE
FOR TRACTORS \geq CV 75 - 55 KW



Basic standard equipment with:

- Sheet steel hot galvanized frame predisposed for steering drawbar
- High density polyethylene tank complete with level indicator, product mixer and can washing, handwashing tank and circuit washing
- Stainless steel or high density polyethylene distribution devices
- Fan housing made of hot galvanised sheet steel and painted
- Ultra-high performance centrifugal closed blade fan in sheet steel Ø 550 mm, air volume up to 22000 mc/h
- Mechanical step-up gear with oil-bath gears and 2 speed gearbox
- Disengagement and centrifugal clutch on the fan shaft
- Self-priming stainless pump with automatic belt tensioner, flow rate 200 lt/min.
- 2 solenoid valves with electrical remote control
- Litre-counter dispensers with graduated scale in stainless steel for each sector



BASIC STANDARD EQUIPMENT

OPTIMA.1500	Tank lt. 1500 Rubber 10.0/75 – 15.3
OPTIMA.2000	Tank lt. 2000 Rubber 10.0/75 – 15.3

ACCESSORIES ON REQUEST ORDERED AND INSTALLED AT THE ORIGIN

ACCESS.64	Universal joint cv 60-1000 mm
ACCESS.64.OM	Universal constant-velocity joint cv 60-1000 mm
ACCESS.15	Fill tube (filter and bottom valve)
ACCESS.42	Hydraulic movement of the upper distribution devices equipped with hydraulic lines with quick coupling
ACCESS.70.V4	4 solenoid valves V.M.A. to control liquid opening-closing
ACCESS.70.A4	4 solenoid valves ARAG to control liquid opening-closing
ACCESS.25	Electrical pressure regulator with remote control
ACCESS.EL	Electrostatic system for the positive charge of the treatment flow

DISTRIBUTION DEVICES AND LITRE-COUNTER DISPENSERS WITH GRADUATED SCALE STAINLESS STEEL WITH ANTIDRIP DEVICE

	<p>BIG.T.SR55</p>	<p>2 guns and pair of stainless fans with hydraulic movement</p>
	<p>BIG.2C.2M4+4</p>	<p>2 guns 2 central hands 4+4 diffusers</p>

NEW LITRE-COUNTER DISPENSERS IN STAINLESS STEEL WITH GRADUATED SCALE FOR EACH SECTOR PROVIDED WITH THE EQUIPMENT



MODEL	minimum height	standard height	variable height	width	length	weight
OPTIMA	145 cm	160 cm	-	152 cm	400 cm	550 kg