

Basic standard equipment with:

- Hot galvanised steel frame treated with high-grip base, metallic paint and transparent protection
- Central and side protection, height-adjustable hubs
- High density polyethylene tank complete with product mixer, level indicator, handwashing tank, circuit washing and can washing
- Steering capability 220°
- Pressure gauge and manual pressure regulator
- 2 solenoid valves with electrical remote control for opening/closing
- Fan housing made of hot galvanised sheet steel and painted
- Ultra-high performance centrifugal closed blade fan in sheet steel Ø 550 mm, air volume up to 22000 mc/h
- Mechanical step-up gear with oil-bath gears and 2 speed gearbox
- Disengagement and centrifugal clutch on the fan shaft
- Self-priming stainless pump with automatic belt tensioner, flow rate 200 lt/min.
- Central distribution device with columns with steerable devices
- Upper distribution devices with electrohydraulic control lattice for: opening, closing, adjusting height, width and vertical direction of diffusers with 70° angle

BASIC STANDARD EQUIPMENT WITH 1 REAR COLUMN

POWER.55.12.A1000	Tank lt. 1000 Rubber 10.0/75 – 15.3
POWER.55.12.A1500	Tank lt. 1500 Rubber 10.0/75 – 15.3
POWER.55.12.A2000	Tank lt. 2000 Rubber 10.0/75 – 15.3

BASIC STANDARD EQUIPMENT WITH 2 REAR COLUMNS ONLY FOR ROWS EXCEEDING 2.30 METRES

POWER.55.12.B1000	Tank lt. 1000 Rubber 10.0/75 – 15.3
POWER.55.12.B1500	Tank lt. 1500 Rubber 10.0/75 – 15.3
POWER.55.12.B2000	Tank lt. 2000 Rubber 10.0/75 – 15.3

ACCESSORIES ON REQUEST ORDERED AND INSTALLED AT THE ORIGIN

ACCESS.52	Universal joint cv 60-700 mm
ACCESS.15	Fill tube (filter and bottom valve)
ACCESS.25	Electrical pressure regulator with remote control
ACCESS.26.M	4-way electronic computer for automatic feed control provided with membrane pump
ACCESS.41	Rubberising difference 400/60 - 15.5 to 6 holes
ACCESS.63	Puncture treatment for pair of wheels
ACCESS.70.V4	4 V.M.A. solenoid valves to control liquid opening-closing
ACCESS.70.A4	4 solenoid valves ARAG to control liquid opening-closing
ACCESS.69	6-fan columns with independent closing the air
ACCESS.ELM	Electrostatic system for the positive charge of the treatment flow
OMOLOGAZIONE.POWER	For road circulation, full load only trolleys lt. 1000, empty trolleys lt. 1500 and 2000, with direct coupling to the tractor (special drawbar, lights, foot rest, license plate holder)

MODEL	minimum height	standard height	variable height	width	length	weight
Power 55-12	220 cm	280 cm	-	220 cm	140 cm	450 kg