

Sting

LT 300 - LT 400

MOUNTED LOW VOLUME ATOMIZER
POLYETHYLENE RANGE
FOR TRACTORS \geq CV 45-33 KW



Basic standard equipment with:


- Frame in tubular steel predisposed for pair of wheels
- Tank in high density polyethylene lt. 300 or lt. 400 complete with product mixer, level indicator, plant washing and handwashing tank
- Distribution devices in high density polyethylene with vertical movement of 70°
- Fan housing in high density polyethylene with two independent outputs
- Centrifugal closed blade fan in sheet steel Ø 500 mm, air volume up to 11750 mc/h, output air speed up to 70 m/sec
- Mechanical step-up gear with oil-bath gears and 2 speed gearbox
- Disengagement and centrifugal clutch on the fan shaft
- Self-priming stainless pump with automatic belt tensioner, flow rate 200 lt/min. 0-6 bar
- 2 Solenoid valves with remote electrical control, pressure gauge and manual pressure regulator
- Litre-counter dispensers with graduated scale in stainless steel for each sector

BASIC STANDARD EQUIPMENT





STING.300	Tank lt. 300 in high density polyethylene
STING.400	Tank lt. 400 in high density polyethylene

ACCESSORIES ON REQUEST ORDERED AND INSTALLED AT THE ORIGIN

ACCESS.08	Universal joint cv 60-800 mm
ACCESS.15	Fill tube (filter and bottom valve)
ACCESS.02	Pair of wheels with hubs
ACCESS.70.V	4 V.M.A. solenoid valves to control liquid opening-closing
ACCESS.70.A	4 solenoid valves ARAG to control liquid opening-closing
ACCESS.56	Hydraulic movement of the upper distribution devices equipped with hydraulic lines with quick coupling
ACCESS.EL	Electrostatic system for the positive charge of the treatment flow



DISTRIBUTION DEVICES IN HIGH DENSITY POLYETHYLENE PROVIDED WITH LITRE-COUNTER DISPENSERS WITH GRADUATED SCALE IN STAINLESS STEEL WITH ANTIDRIP DEVICE

	2V.ST	2 lower fans (8 sectors in stainless steel)
	2C2V.ST	2 upper guns 2 lower fans (8 sectors in stainless steel)
	4V.ST	SSDVVRVVDVVV RDVVRVVDVVV
	3T.ST 3TG.ST	GDDPRP GVSVDGGDV GDDDGVP RP GVSVDGGDV

NEW LITRE-COUNTER DISPENSERS IN STAINLESS STEEL WITH GRADUATED SCALE FOR EACH SECTOR PROVIDED WITH THE EQUIPMENT



MODELLO	altezza minima	altezza standard	altezza variabile	larghezza	lunghezza	Peso
Sting 50	130 cm	230 cm	-	100 cm	150 cm	260 kg