

Star 50 LT 1000



LOW VOLUME TOWED ATOMIZER
STAINLESS RANGE FOR
TRACTORS \geq CV 75 - 55 KW



Basic standard equipment with:

- Sheet steel hot galvanized frame predisposed for steering drawbar
- Tank in high density polyethylene lt. 1000 complete with level indicator, product mixer and can washing, handwashing tank and circuit washing
- Stainless steel distribution devices with vertical movement of 70°
- Fan housing made of steel
- Centrifugal closed blade fan in sheet steel Ø 500 mm, air volume up to 18000 mc/h
- Mechanical step-up gear with oil-bath gears and 2 speed gearbox
- Disengagement and centrifugal clutch on the fan shaft
- Self-priming stainless pump with automatic belt tensioner, flow rate 200 lt/min.
- 2 Solenoid valves with remote electrical control, pressure gauge and manual pressure regulator
- Litre-counter dispensers with graduated scale in stainless steel for each sector

DISTRIBUTION DEVICES AND LITRE-COUNTER DISPENSERS WITH GRADUATED SCALE STAINLESS STEEL WITH ANTIDRIP DEVICE

	<p>2C2V.SR50</p>	<p>2 upper guns 2 lower fans (8 sectors in stainless steel)</p>
	<p>4V.SR50</p>	<p>2 upper fans 2 lower fans (8 sectors in stainless steel)</p>
	<p>3T.SR50 3TG.SR50</p>	<p>Vertical movement hydraulic gun with 3 dispensers and hydraulic lines Vertical and swivel movement hydraulic gun with 3 dispensers and hydraulic lines</p>

NEW LITRE-COUNTER DISPENSERS IN STAINLESS STEEL WITH GRADUATED SCALE FOR EACH SECTOR PROVIDED WITH THE EQUIPMENT



MODEL	minimum height	standard height	variable height	width	length	weight
Star 50	155 cm	255 cm	-	138 cm	300 cm	380 kg